Arcadia White

Cabinet Specifications

Face Frames

Face Frames are $\frac{3}{4}$ " * 1 $\frac{1}{2}$ " solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.

Tops & Bottoms

Tops and bottom panels are ½" thick multi-ply hardwood plywood. Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ "thick.

Toe kicks shall be ½" thick hardwood plywood.

4 End Panels

End panels are ½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$. (5) Adjustable Shelves

Adjustable shelves are 5/8" thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)

6 Back Panels

Back are ½"thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

(7) Shelf Clips

Shelf clips are 6mm bore with a fluted Metal clips. Shelved are adjustable on $2\frac{1}{2}$ increments.

Doors

3/4"HDF door styles with flat panels.

Full Overlay , Concealed, 110 degree opening, with soft closing dampers.

Drawer Boxes

 $\frac{5}{8}$ solid hardwood front, back and 2 sides with $\frac{3}{8}$ plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides ..(Exceeds industry standards)

Base Corner Brackets

High impact, injection molded plastic .

Hanging Strips

Hanging strip are 3/4" *11/4" hardwood.



