Frontier Shaker

Cabinet Specifications



Face Frames

Face Frames are $\frac{3}{4}$ * 1 $\frac{1}{2}$ solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails.Frames are dadoed to received cabinet ends,top, and bottoms.

Tops & Bottoms

½" thick multi-ply hardwood plywood . Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ " thick.

Toe Kicks

 $\frac{1}{2}$ " thick hardwood plywood.

4 End Panels

½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$.

Adjustable Shelves

3/4" thick multi-ply hardwood Plywood. Edge banded with wood tapes.(Exceeds industry standards.)

6 Back Panels

½" thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

on $2\frac{1}{2}$ increments.

® Doors

3/4" Solid hard wood door stiles with flat central panel, shaker.

(9) Full Overlay , Concealed, 110 degree opening, with soft closing dampers.

Drawer Boxes

 $\frac{3}{4}$ "solid hardwood front, back and 2 sides with $\frac{3}{8}$ " plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides .. (Exceeds industry standards)

Base Corner Brackets

High impact, injection molded plastic .

Hanging Strips

3/4" *11/4" hardwood.



