## Mojave Shaker

## Cabinet Specifications



Face Frames

Face Frames are  $\frac{3}{4}$  \* 1  $\frac{1}{2}$  solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.

 $2 \frac{\text{Tops \& Bottoms}}{\text{Tops and bottom panels are } \frac{1}{2}\text{" thick multi-ply hardwood} }$ plywood . Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are  $\frac{3}{8}$ "thick.

 $\begin{tabular}{ll} \hline 3 & {\hbox{Toe Kicks}} \\ \hline {\hbox{Toe kicks shall be} $\frac{1}{2}$" thick hardwood plywood .} \\ \hline \end{tabular}$ 

End panels are ½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed  $\frac{3}{16}$ . (5) Adjustable Shelves

Adjustable shelves are ½" thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)

Back are ½"thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. ( Exceeds industry standards.)

(7) Shelf Clips

Shelf clips are 6mm bore with a fluted Metal clips. Shelved are adjustable on  $2\frac{1}{2}$  increments.

 $\frac{3}{4}$ "HDF door styles with flat panels.

Hinges

(9) Full Overlay , Concealed, 110 degree opening, with soft closing dampers.

Drawer Boxes

 $\frac{5}{8}$  solid hardwood front, back and 2 sides with  $\frac{3}{8}$  plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides .. (Exceeds industry standards)

Base Corner Brackets

High impact, injection molded plastic .

Hanging Strips

Hanging strip are  $\frac{3}{4}$ " \*1 $\frac{1}{4}$ " hardwood.



