Nantucket Linen

Cabinet Specifications

Face Frames

Face Frames are $\frac{3}{4}$ * 1 $\frac{1}{2}$ solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.

 $2 \hline \frac{\text{Tops \& Bottoms}}{\frac{1}{2}\text{"thick multi-ply hardwood plywood . Tops and bottoms}}$ are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ " thick.

Toe Kicks

½" thick hardwood plywood.

4 End Panels $\frac{1}{2}$ " thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$.

Adjustable Shelves

3/4" thick multi-ply hardwood Plywood. Edge banded with wood tapes.

(Exceeds industry standards.)

6 Back Panels

 $\frac{1}{2}$ thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet.

(Exceeds industry standards.)

(7) Shelf Clips

6mm bore with a fluted Metal clips. Shelved are adjustable on $2\frac{1}{2}$ increments.

Doors

³/₄"HDF door styles with straight top raised panels.

9 Full Overlay , Concealed, 110 degree opening, Soft close.

Drawer Boxes

5/8 solid hardwood front, back and 2 sides with 3/8 plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides .. (Exceeds industry standards)

Base Corner Brackets

High impact, injection molded plastic .

Hanging Strips

3/4"*11/4" hardwood.



